

Drevoil ATF III

Application

Specifications

Typicals

A very high graded automatic transmission fluid formulated with solvent refined and synthetic base oils and a number of selected additives to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- very good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured

This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF, IIIG or IIHH fluid is required.

Performance level:
Aisin Warner JWS 3309(T-IV)
Allison C4 / TES-389
BMW 7045E / 8072B / LA2634 / LT71141
Cat TO-2
DTFR 13C100 / 13C110 / 13C140 / 13C170 / 38B100
Ford Mercon / M2C138-CJ / 166-H
GM Dexron IID / IIE / IIIF / IIIG / IIHH / TASA
Hyundai/Kia/Mitsubishi SP-III
MAN 339 Typ Z1 / V1 / Z2
MB 236.1 / 236.3 / 236.5 / 236.6
MB 236.7 / 236.9 / 236.10 / 236.11 / 236.93
Nissan Matic D/J/K
Toyota T-III / T-IV
Voith 55.6335 (G607)
Volvo 97340 / 97341 (AT101) / 1161540
VW G 052 025 / 052 090 / 052 162
ZF TE-ML 02F/03D/04D/09/11A/11B/14A/14B/16L/17C

Density at 15 °C, kg/l	0,848
Viscosity 40 °C, mm²/s	36,00
Viscosity 100 °C, mm²/s	7,30
Viscosity Index	175
Flash Point COC, °C	226
Pour Point, °C	-48