

Drevoil ATF ULV

Application

A very high graded, extremely low-viscosity automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- excellent contribution to fuel economy
- excellent lubrication
- very good resistance against oxidation
- very good thermal stability
- excellent and very stable friction characteristics
- excellent resistance against corrosion and foaming
- excellent protection against wear
- a very high and stable viscosity index
- without colorant.

Specifications

This premium oil is specially developed for the lubrication of specific automatic transmissions, including certain Mercedes-Benz 9-speed automatic transmissions. This product contributes significantly to fuel economy.

*For information: this product was previously known as ATF 9G.*

Performance level:  
Aisin Warner AW-2  
BMW 83 22 2 413 477 (ATF7)  
Mazda ATF A7  
MB 236.15 / 236.16 / 236.17  
Nissan Matic P  
Ford Mercon ULV / M2C949-A  
GM Dexron ULV ATF  
VW G 053 001

Typicals

Density at 15 °C, kg/l	0,840
Viscosity 40 °C, mm²/s	19,60
Viscosity 100 °C, mm²/s	4,64
Viscosity Index	162
Flash Point COC, °C	188
Pour Point, °C	-51