

Drevoil Euro Line 5W30

LB Specialsynth D 5W30 is a product of the LB (Level Back-up) product range. These products are based on the officially approved formulas, using the same high-quality additives, but the base oils have been replaced with equivalent alternatives. This creates equivalent products in terms of quality, with a performance level corresponding to the originally approved products. However, because no field tests have been conducted, the product may be claimed only to meet the mentioned performance levels.

Application

This synthetic, universal, fuel economy, "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

Specifications

Performance level:
ACEA C2, C3
API SP
BMW Longlife-04
Fiat 9.55535-S1
GM dexos 2
MB 229.31 / 229.51 / 229.52
Opel OV 040 1547 - D30 / G30
VW 505.00 / 505.01

Typicals

Density at 15 °C, kg/l	0,855
Viscosity -30 °C, mPa.s	6100
Viscosity 40 °C, mm²/s	72,50
Viscosity 100 °C, mm²/s	12,20
Viscosity Index	168
Flash Point COC, °C	222
Pour Point, °C	-42
Total Base Number, mgKOH/g	7,5
Sulphate Ash, %	0,74