

Drevoil Fleet Guard 15W40 TBN 16

A diesel engine oil, formulated with solvent refined base oils and a well-balanced choice of additives. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against corrosion and foam
- a high and stable viscosity index
- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners.

Application

This engine lubricant is applicable to diesel engines (normally- or turbo-aspirated) even under tough operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This product is suitable for application in Euro 4 and Euro 5 engines.

Specifications

Performance level:
 ACEA E7
 API CI-4 / SL
 Cat ECF-1-a / ECF-2
 Cummins CES 20077/20078
 Detroit Diesel 93K215
 Deutz DQC III-18
 DTFR 15B110
 Global DHD-1
 JASO DH-1
 Mack EO-N/EO-M Plus
 MAN M 3275-1
 MB 228.3
 MTU Type 2
 Renault VI RLD-2
 Volvo VDS-3
 Allison C3, CAT TO-2
 ZF 04C / 04P / 07C / 07D / 21K

Typicals

Density at 15 °C, kg/l	0,886
Viscosity -20 °C, mPa.s	6300
Viscosity 40 °C, mm²/s	110,30
Viscosity 100 °C, mm²/s	14,50
Viscosity Index	135
Flash Point COC, °C	212
Pour Point, °C	-30
Total Base Number, mgKOH/g	16,1
Sulphate Ash, %	2,00