

Drevoil Fleet Guard 20W50 TBN 16

A diesel engine oil, formulated with solvent refined base oils and a well-balanced choice of additives. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
 a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against corrosion and foam
- a high and stable viscosity index
- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners.

Application

This engine lubricant is applicable to diesel engines (normally- or turbo-aspirated) even under tough operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This product is suitable for application in Euro 4 and Euro 5 engines.

Specifications

Performance level:

ACEA E7 API CI-4 / SL

Cummins CES 20077 / 20078

Deutz DQC III-18 DTFR 15B110 Global DHD-1 MB 228.3

Typicals

Density at 15 °C, kg/l	0,893
Viscosity -15 °C, mPa.s	6000
Viscosity 40 °C, mm ² /s	156,00
Viscosity 100 °C, mm ² /s	17,50
Viscosity Index	127
Flash Point COC, °C	242
Pour Point, °C	-30
Total Base Number, mgKOH/g	16,5
Sulphate Ash, %	2,00